

# MODEL 340/340TS FIRE TRANSMITTER



## OVERVIEW

The Model 340/340TS Fire Transmitters are addressable transmitters designed specifically for connection to initiating devices, sprinkler flow and supervisory switches, and other UL miscellaneous accessories with normally open contacts. The Model 340/340TS Fire Transmitters are UL 864 listed.

In addition to the supervisory features such as low battery, tamper, and end of line violation, the Models 340/340TS also meet the 200 second polling requirement while providing the option of either a Style 1 or Style 2 wiring configuration.

The Models 340/340TS Fire Transmitters utilize FHSS (Frequency Hopping Spread Spectrum) signaling technology and provides bi-directional system communication to assure a secure and reliable network.

Both easy to install and cost effective, the low profile Model 340 incorporates a built in transmitter and is ideal for applications such as monitoring of flow and tamper switches, connection to existing hardwired panel outputs, PIV monitoring, and a host of other connections utilizing minimal wiring from the desired connection to the transmitter.

The 340TS is available for installations requiring horizontal mounting.

## FEATURES

- **UL 864 9th Edition Listed**
- Selectable Style 1 or Style 2 Wiring
- Bi-Directional RF Communication
- Operates on a Single 3V Lithium Battery
- Fully Supervised
- 900 MHz Band FHSS Transmission Format



UL Listed

NFPA Approved

CSFM Approved

NY Fire Department Approved

FIRE DETECTION TECHNOLOGY. RE-INVENTED.

only at [www.wirelessfirealarm.com](http://www.wirelessfirealarm.com)

## MODEL 340/340TS FIRE TRANSMITTER



### SPECIFICATIONS

- Battery Type: 3 Volt Lithium Duracell DL123A or Panasonic CR123A
- Battery Life: 12 Months Minimum
- Battery Replacement: Upon Low battery report and/or during annual maintenance
- Testing: Follow this manual and NFPA 72 or local requirements
- Low Battery: 2.70 volts nominal
- Initiating loop rating: 3 Vdc, 1ma
- Transmission: Complies to FCC Part 15
- Test Transmission: 200 second supervisory polling
- Compatibility: Commercial Wireless Systems International, LLC Model CP-3000

Height 4.75" | Width 2.55" | Depth 1.58" | Weight 6.4 oz.

